

**FEATURES:**

- 6-7/8" square plates
- 3 degree tilt for more comfortable sitting position
- memory spring returns swivel to original position
- 13 gauge steel
- elongated mounting slots 5-1/4" on center
- screws for mounting not included (#14 gauge pan head screw is recommended)
- only recommended for stools with backs
- 3/4" thick at back, 1-1/8" thick at front


**APPLICATION:**

A deluxe swivel for chairs or bar stools.

**SPECIFICATIONS:**

**INSTALLATION:**

1. Rotate plates at 45° to each other so that corner slotted holes are exposed.
2. Place swivel on base material (platform) and position for mounting. Using a pencil, mark off corner screw slots and outside corners of plates on base.
3. Make indent with scratch awl in center of screw slots. Drill pilot holes for screws. Also bore 1/2" diameter access hole.
4. Attach lower swivel plate to base with screws.
5. Place seat or turn table upside down on bench. Turn base and mounted swivel upside down and place it down on turn table of seat. Use pencil and mark screw slots as done before in step #2.
6. Make indent on slot centers and drill pilot holes.
7. Reposition upper swivel plate on seat/turn table underside and attach upper plate with screws through 1/2" access hole. A magnetic tipped screw driver would be helpful.



*The 3° tilt gives a more comfortable sitting position.*

