

**APPLICATION:**

Woodturner's Finish is a ready to use, high sheen padding finish, especially formulated for use on round wooden objects. Woodturner's Finish (and a white cloth) applies a high sheen finish while the project is still on the lathe. Woodturner's Finish may be applied to raw wood or cured finish.

**FEATURES:**

- Great for finishing wooden: Turnings – Spindles - Lamp Bases - Pool Cues - Wood Candle Sticks
- Shellac and resin based formula
- Rejuvenates almost any cured finish

**DIRECTIONS:**

***Read, understand, and follow all safety instructions on the product label***

1. New wood (cured finish) should be sanded to 360 grit smoothness.
2. Remove all dust and grime with tack cloth or vacuum hose.
3. Use a lint free white cloth shaped into a firm hand size pad.
4. Apply enough Woodturner's Finish to dampen the pad. Then flatten the pad against the palm of your hand to insure equal distribution of finish.
5. As the wooden object slowly rotates in the lathe, slowly move the pad across the surface with a firm, not hard, pressure. (Note: on raw wood the pad may need to be rewetted at least once)
6. Once the surface has been uniformly coated (do not flood), stop lathe and allow at least a one (1) hour dry time.
7. If additional coats are desired or needed due to uneven sheen (possibly caused by wood absorption) follow steps 3 through 6.
8. If a higher sheen is desired, use the dried application pad as a buffing cloth, apply firm pressure and slowly move across the surface while the finished piece slowly rotates in the lathe.
9. Allow the piece to set in a warm (72°F) dust free environment overnight to allow for proper curing. Note: If a dull effect is desired use 4/0 steel wool or nylon mesh pad after the finish has cured.
10. Clean up with H. Behlen 710 Solvent or Behkol Solvent.

